

Appl. No. 10/604,862
Amdt. dated July 19, 2006
Reply to Office action of April 19, 2006

Amendments to the Claims:

1. (currently amended) A high-speed optical recording apparatus in an optical storage
device for generating a write signal according to an RLL modulation waveform
5 inputted to the high-speed optical recording apparatus, so as to control a writing
power of a pickup in the optical storage device, the recording apparatus comprising:
a clock generator for generating a first clock signal;
an adjustment data storage unit for storing a plurality of sets of write strategy
parameters, and selecting and outputting a corresponding set of write strategy
10 parameters from plurality of the sets of write strategy parameters according to
the RLL modulation waveform;
a rough delay unit electrically connected to the clock generator to receive the first
clock signal, and further electrically connected to the adjustment data storage
unit to receive the selected set of write strategy parameters, the rough delay
15 unit for generating a fine delay parameter according to the selected set of write
strategy parameters, and for delaying the RLL modulation waveform
according to the first clock signal and the selected set of write strategy
parameters to generate a first delay signal; and
a fine delay chain electrically connected to the rough delay unit to receive the first
20 delay signal and the fine delay parameter, the fine delay chain for delaying the
first delay signal according to the fine delay parameter so as to generate the
write signal, the fine delay chain having a plurality of serially connected delay
cells, each delay cell delaying the first delay signal by a predetermined period;
wherein the RLL modulation waveform is an NRZI modulation waveform, the
25 apparatus generating the write signal according to an encoded modulation bits;
and
the clock generator further generates a second clock signal, the recording apparatus
further comprising:

Appl. No. 10/604,862
Amdt. dated July 19, 2006
Reply to Office action of April 19, 2006

- 5 a delay adjustment state machine electrically connected to the clock generator
 to receive the second clock signal, and further electrically connected to
 the adjustment data storage unit to receive the selected set of write
 strategy parameters, the delay adjustment state machine for generating a
 rough delay parameter and the fine delay parameter according to the
 selected set of write strategy parameters, and for delaying the NRZI
 modulation waveform according to the second clock signal and the set
 of write strategy parameters so as to generate a second delay signal; and
10 a rough delay counter or a rough delay shift register electrically connected to
 the clock generator to receive the first clock signal, and further
 electrically connected to the delay adjustment state machine to receive
 the second delay signal in order to delay the second delay signal
 according to the first clock signal, and to receive the rough delay
 parameter so as to generate the first delay signal.
- 15 2. (cancelled)
3. (cancelled)
- 20 4. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 3~~
 wherein clock generator comprises a phase locked loop for generating the first clock
 signal, and a frequency divider for dividing a frequency of the inputted first clock
 signal to generate the second clock signal.
- 25 5. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 3~~
 wherein a period of the second clock signal is equal to a base period of the RLL
 modulation waveform.

Appl. No. 10/604,862
Amdt. dated July 19, 2006
Reply to Office action of April 19, 2006

6. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 3~~ wherein a period of the second clock signal is equal to a multiple of a period of the first clock signal.
- 5 7. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 3~~ wherein a resolution of the delay adjustment state machine delaying the RLL modulation waveform is equal to a period of the second clock signal.
- 10 8. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 3~~ wherein the rough delay counter comprises a counter, and a comparator.
- 15 9. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 3~~ wherein a resolution of the rough delay counter delaying the second delay signal is equal to a period of the first clock signal.
10. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 2~~ further comprising an NRZI input interface for receiving the NRZI modulation waveform and generating an address signal.
- 20 11. (original) The high-speed optical recording apparatus of claim 10 wherein the EFM input interface generates the address signal according to a previous land section, a current pit section, and a next land section in the EFM modulation waveform.
- 25 12. (original) The high-speed optical recording apparatus of claim 10 wherein the rough delay unit is electrically connected to the NRZI input interface to receive the NRZI modulation waveform.
13. (original) The high-speed optical recording apparatus of claim 10 wherein the

Appl. No. 10/604,862
Amdt. dated July 19, 2006
Reply to Office action of April 19, 2006

adjustment data storage unit is electrically connected to the EFM input interface to receive the address signal for selecting the corresponding write strategy parameter according to the address signal.

- 5 14. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 2~~ further comprising a data storage setting interface electrically connected to the adjustment data storage unit, and further electrically connected to a microprocessor of the optical storage device to receive the sets of write strategy parameters and storing the sets of write strategy parameters into the adjustment data storage unit.
- 10 15. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 2~~ wherein the adjustment data storage unit is a volatile memory.
- 15 16. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 2~~ wherein the delay cells are a plurality of serially connected inverters or buffers, the fine delay chain further comprising a multiplexer for selecting the write signal from a plurality of outputs of the inverters or buffers.
- 20 17. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 2~~ wherein a resolution of the fine delay chain delaying the first delay signal is equal to the predetermined period.
- 25 18. (currently amended) The high-speed optical recording apparatus of claim 1 ~~claim 2~~ wherein the EFM modulation waveform is generated by an EFM encoder of the optical storage device.